

# Daisy

## Case Features:

- Available for Meat, Fish & Cheese, Salad, Prepared Foods, Deli, Pastry, Bread, Grab-n-Go
- LED light technology enhances presentation
- Available in multiple lengths and glass angles for perfect space planning
- Fully Refrigerated/ Dry/ Neutral
- Choice of Colors/Laminates and Finishes for the front case decoration

Plug Type  
(All Models)




6-15P




## HEATED

## REFRIGERATED


### HEATED VENTILATED




DAQV




DAQ




DVM




DSM  
Remote only




DVSF



DVS




DCER90




DCIR90

### BAIN MARIE




DBM

### DRY HEATED DECK




DTA

### SALADS




DSLS


### GELATO




DGL




DVSG



DVT



DCER45



DCIR45

## DISPLAY CASES

Type	Model	Width	Depth	Height	Electrical Requirements	
<b>REFRIGERATED</b> (with Storage)	DVT-1250	51.6" (1310mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps	
	DVT-1562	63.9" (1622mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/6 Amps	
	DVT-1875	76.2" (1935mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/7 Amps	
	DVT-2500	100.8" (2560mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/8 Amps	
	Remote only ->	DVT-3125	125.4" (3185mm)	42" (1067mm)	47.2" (1200mm)	220V/1Phase/60Hz/14 Amps
	Remote only ->	DVT-3750	150" (3810mm)	42" (1067mm)	47.2" (1200mm)	220V/1Phase/60Hz/13 Amps
<b>REFRIGERATED</b> (without Storage) <b>DVSG - Pull out Drawer</b>	DVS/DVSG-937	39.25" (997mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/4 Amps	
	DVS/DVSG-1250	51.6" (1310mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps	
	DVS-1562	63.9" (1622mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/6 Amps	
	DVS/DVSG-1875	76.2" (1935mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/7 Amps	
	DVS/DVSG-2500	100.8" (2560mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/8 Amps	
	Remote only ->	DVS/DVSG-3125	125.4" (3185mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/14 Amps
	Remote only ->	DVS/DVSG-3750	150" (3810mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/13 Amps
	<b>External 90° Angle</b>	DCER90	42" (1078mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps
	<b>External 45° Angle</b>	DCER45	32.5" (825mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps
	<b>Internal 90° Angle</b>	DCIR90	32.7" (830mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/6 Amps
<b>Internal 45° Angle</b>	DCIR45	28" (708mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps	
<b>GELATO</b>	DGL-937 (10 flavors)	39.25" (997mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/7 Amps	
	DGL-1250 (14 flavors)	51.6" (1310mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/7 Amps	
	DGL-1562 (16 flavors)	63.9" (1622mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/8 Amps	
	DGL-1875 (20 flavors)	76.2" (1935mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/8 Amps	
<b>SALADS</b>	DSLS-1250	51.6" (1310mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps	
	DSLS-1875	76.2" (1935mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/7 Amps	
<b>GRAB 'N' GO</b> (Refrigerated) DSM - Flat front panel (all models are remote) DVSF - Low Glass (Note: height difference)	DVM/DSM/DVSF-937	39.25" (997mm)	42" (1067mm)	47.25" (1200mm) / 34" (860mm)	220V/1Phase/60Hz/4 Amps	
	DVM/DSM/DVSF-1250	51.6" (1310mm)	42" (1067mm)	47.25" (1200mm) / 34" (860mm)	220V/1Phase/60Hz/5 Amps	
	DVM/DSM/DVSF-1562	63.9" (1622mm)	42" (1067mm)	47.25" (1200mm) / 34" (860mm)	220V/1Phase/60Hz/6 Amps	
	DVM/DSM/DVSF-1875	76.2" (1935mm)	42" (1067mm)	47.25" (1200mm) / 34" (860mm)	220V/1Phase/60Hz/7 Amps	
	DVM/DSM/DVSF-2500	100.8" (2560mm)	42" (1067mm)	47.25" (1200mm) / 34" (860mm)	220V/1Phase/60Hz/8 Amps	
	Remote only ->	DVM/DSM/DVSF-3125	125.4" (3185mm)	42" (1067mm)	47.25" (1200mm) / 34" (860mm)	220V/1Phase/60Hz/14 Amps
	Remote only ->	DVM/DSM/DVSF-3750	150" (3810mm)	42" (1067mm)	47.25" (1200mm) / 34" (860mm)	220V/1Phase/60Hz/14 Amps
	<b>GRAB 'N' GO</b> (Heated)	DAQ-937	39.25" (997mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/9 Amps
DAQ-1250		51.6" (1310mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/12 Amps	
<b>HEATED VENTILATED</b>	DAQV-1250	51.6" (1310mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps	
	DAQV-1875	76.2" (1935mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/7 Amps	
<b>DRY HEATED DECK</b>	DTA-1250	39.25" (997mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps	
	DTA-1875	76.2" (1935mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/7 Amps	
<b>BAIN MARIE</b>	DBM-1250	51.6" (1310mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/5 Amps	
	DBM-1875	76.2" (1935mm)	42" (1067mm)	47.25" (1200mm)	220V/1Phase/60Hz/7 Amps	

All technical data, pictures and drawings contained in this document are not binding on the manufacturer, nor can the manufacturer be held liable for any modification of the machine, in part or in whole.