

UNITED HEATED

REFRIGERATED | PACKAGED FOOD | BEVERAGES



Project: _____ Item #: _____
Location: _____ Approved: _____

631-981-2100

Heated Merchandiser

Standard Features:


- Available in various size configurations
- Ventilated heating system
- Tempered thermo dynamic glass side panels
- Stainless steel exterior/ interior, standard
- 4 shelves + base, 5 level merchandising
- Easy accessible temperature control panel
- LED lighting
- Adjustable stainless steel shelves, flat or slanted
- cord and plug (10ft cord)
- 3" heavy duty casters




GRAB AND GO HEATED DISPLAY CASE

Technical drawing of the front view of the 1000 Series 24" unit. The unit is shown with its dimensions: a width of 27" (685 mm) and a height of 31.5" (800 mm). The drawing shows a front panel with a handle and a lock mechanism.

UH-625




UH-937



4.1. Digital control

	Model #	Dimensions W x D x H (In.)	Net Wt. (Lbs.)	Amps.	Nema Plug	Capacity (Cu. Ft.)
Heated	UH-625	27" x 31.5" x 78.5"	381	10.5	6-20P	18.09
	UH-937	39.25" x 31.5" x 78.5"	530	14	6-20P	24.15



Important Notes: Performance issues (product temperatures, water on floor, etc.) caused by adverse conditions are not covered by warranty.
Keep unit at least 15' from exterior doors, overhead HVAC vents, or any air curtain disruption.
Do not expose unit to direct sunlight or any heat source (ovens, fryers, etc.).
Tile floors, low ceilings, or small rooms will increase noise level.
Compressor air lower front intake. Front panel cannot be blocked.

All technical data, pictures and drawings contained in this document are not binding on the manufacturer, nor can the manufacturer be held liable for any modification of the machine, in part or in whole.