

VISTA

HEATED | PREPARED FOODS

gti **DESIGNS**

Project: _____ Item #: _____

Location: _____ Approved: _____

631-981-2100

Heated Display Case


Standard Features:

- Ventilated heated
- Three shelves with grids and stainless steel deck
- Thermo pane glass
- LED lighting
- Electronic digital control panel
- White exterior, RAL 9003
- Straight Glass (VD)
- Glass side panels
- Adjustable equipment legs
- Cord & Plug (6ft cord)
- Rear sliding doors, hinged doors for 24" and 33.75" cases



Optional Accessories:

- Channel Kit (to seam two separate cases together without side panels)
- Curved glass (VC)
- Caster kit (add 3" to height)
- Paint exterior panels, customer choice of RAL color




VISTA


HEATED DISPLAY CASE




Top View



Side View





Rear View



Technical Specifications & Electrical Requirements

Glass Style	Model #	Dimensions W x D x H (In.)	Net Wt. (Lbs.)	Amps.	Nema Plug	Capacity (Cu. Ft.)
Straight Glass (VD)	VAQ-600 VD	24" x 31.25" x 51.25"	395	6	6-15P	4.83
	VAQ-850 VD	33.75" x 31.25" x 51.25"	468	9	6-15P	6.85
	VAQ-1250 VD	49.5" x 31.25" x 51.25"	611	13	6-15P	10.07
Curved Glass (VC)	VAQ-600 VC	24" x 31.25" x 51.25"	395	6	6-15P	4.83
	VAQ-850 VC	33.75" x 31.25" x 51.25"	468	9	6-15P	6.85
	VAQ-1250 VC	49.5" x 31.25" x 51.25"	611	13	6-15P	10.07



Important Notes: Performance issues (product temperatures, water on floor, etc.) caused by adverse conditions are not covered by warranty. Keep unit at least 15' from exterior doors, overhead HVAC vents, or any air curtain disruption. Do not expose unit to direct sunlight or any heat source (ovens, fryers, etc.). Tile floors, low ceilings, or small rooms will increase noise level. Compressor air lower front intake. Front panel cannot be blocked.

All technical data, pictures and drawings contained in this document are not binding on the manufacturer, nor can the manufacturer be held liable for any modification of the machine, in part or in whole.