VISTA

HEATED | PREPARED FOODS

Project:	Item #:
Location:	Approved:



631-981-2100

Heated Display Case

Standard Features:

- Ventilated heated
- Three shelves with grids and stainless steel deck
- Thermo pane glass
- LED lighting
- Electronic digital control panel
- White exterior, RAL 9003
- Straight Glass (VD)
- Glass side panels
- Pull down night curtain
- Adjustable equipment legs
- Cord & Plug (6ft cord)
- Rear sliding doors, hinged doors for 24" and 33.75" cases

Optional Accessories:

- Channel Kit (to seam two separate cases together without side panels)
- Curved glass (VC)
- Caster kit (add 3" to height)
- Paint exterior panels, customer choice of RAL color






















Top View









Control panel


> Power supply

Side View





Rear View



Technical Specifications & Electrical Requirements

Glass Style Model # Dimensions W x D x H (In.) Net Wt. (Lbs.) Amps. Plug Straight Glass (VD) VAQ-600 VD 24"x 31.25"x 51.25" 395 6 6-15P VAQ-850 VD 33.75" x 31.25"x 51.25" 468 9 6-15P VAQ-1250 VD 49.5" x 31.25"x 51.25" 611 13 6-15P Curved Glass (VC) VAQ-850 VC 24" x 31.25"x 51.25" 395 6 6-15P VAQ-850 VC 33.75" x 31.25"x 51.25" 468 9 6-15P							
Straight Glass VAQ-850 VD 33.75" x 31.25"x 51.25" 468 9 6-15P (VD) VAQ-1250 VD 49.5" x 31.25"x 51.25" 611 13 6-15P Curved Glass (VC) VAQ-850 VC 24" x 31.25"x 51.25" 395 6 6-15P VAQ-850 VC 33.75" x 31.25"x 51.25" 468 9 6-15P	Glass Style	Model #			Amps.		Capacit (Cu. Ft.
Glass (VD) (VD) VAQ-850 VD 33.75" x 31.25"x 51.25" 468 9 6-15P VAQ-1250 VD 49.5" x 31.25"x 51.25" 611 13 6-15P Curved Glass (VC) VAQ-850 VC 24" x 31.25"x 51.25" 395 6 6-15P VAQ-850 VC 33.75" x 31.25"x 51.25" 468 9 6-15P	Ctualabt	VAQ-600 VD	24"x 31.25"x 51.25"	395	6	6-15P	4.83
VAQ-1250 VD 49.5" x 31.25" x 51.25" 611 13 6-15P VAQ-600 VC 24" x 31.25" x 51.25" 395 6 6-15P Curved Glass (VC) VAQ-850 VC 33.75" x 31.25" x 51.25" 468 9 6-15P	Glass	VAQ-850 VD	33.75" x 31.25"x 51.25"	468	9	6-15P	6.85
Curved Glass VAQ-850 VC 33.75" x 31.25"x 51.25" 468 9 6-15P (VC)		VAQ-1250 VD	49.5" x 31.25"x 51.25"	611	13	6-15P	10.07
Glass VAQ-850 VC 33.75" x 31.25"x 51.25" 468 9 6-15P (VC)	Cumred	VAQ-600 VC	24" x 31.25"x 51.25"	395	6	6-15P	4.83
	Glass	VAQ-850 VC	33.75" x 31.25"x 51.25"	468	9	6-15P	6.85
VAQ-1250 VC 49.5 X 31.25 X 51.25" 611 13 6-15P		VAQ-1250 VC	49.5" x 31.25"x 51.25"	611	13	6-15P	10.07





140°F / 149 °F



Nema 6-15P



Important Notes: Performance issues (product temperatures, water on floor, etc.) caused by adverse conditions are not covered by warranty. Keep unit at least 15' from exterior doors, overhead HVAC vents, or any air curtain disruption.

Do not expose unit to direct sunlight or any heat source (ovens, fryers, etc.).

Tile floors, low ceilings, or small rooms will increase noise level.

Compressor air lower front intake. Front panel cannot be blocked.

All technical data, pictures and drawings contained in this document are not binding on the manufacturer, nor can the manufacturer be held liable for any modification of the machine, in part or in whole.