

FUTURO SLIM

REFRIGERATED | PACKAGED FOOD | BEVERAGES



Project: _____ Item #: _____
Location: _____ Approved: _____

631-981-2100

Open Merchandiser

Standard Features:

- Self-contained (floor drain required)
- Ventilated cooling system, with 2 classes of temperature.
- Top mounted LED lighting
- LED lighting under each shelf
- Electronic digital control panel
- White or black interior/exterior
- Double pane glass side panels
- Adjustable shelves - flat or angled
- Standard case - 5 shelves
- Produce case - 2 selves+angled mirror
- Adjustable Equipment Legs
- Price tag moldings
- Night blind



Optional Accessories:

- Channel Kit (to seam two separate cases together without side panels)
- Solid side panels
- Remote (ask for specifications)
- Black, RAL 9005 exterior/ interior




FUTURO MULTIDECK SLIM


GRAB AND GO | REFRIGERATED OPEN MERCHANDISERS




Top View




MF2 700P L/F CG CC-1250



MF2 700P L/F CG CC-1562




MF2 700P L/F CG CC-1875




MF2 700P L/F CG CC-2500⁽¹⁾

- ⚡ Control panel
- ⊕ Drainage point
- ◇ Suction line
- ▷ Power supply

Side View





MF2 700P L CG CC
Standard



MF2 700P F CG CC
Produce

Rear & Front View



Technical Specifications & Electrical Requirements

Type	Model #	Dimensions W x D x H (In.)	Amps.	HP	Capacity (Cu. Ft.)
Standard w/ Night Blinds	MF2 700P L CG CC-1250	52.5" x 29" x 82.25"	9	2 x 3/4	26
	MF2 700P L CG CC-1562	65" x 29" x 82.25"	11	3 x 3/4	32
	MF2 700P L CG CC-1875	77" x 29" x 82.25"	16	4 x 3/4	39
	MF2 700P L CG CC-2500 ⁽¹⁾	102" x 29" x 82.25"	2x 9	4 x 3/4	52
Produce w/ Night Blinds	MF2 700P F CG CC-1250	52.5" x 29" x 82.25"	9	2 x 3/4	26
	MF2 700P F CG CC-1562	65" x 29" x 82.25"	11	3 x 3/4	32
	MF2 700P F CG CC-1875	77" x 29" x 82.25"	16	4 x 3/4	39
	MF2 700P F CG CC-2500 ⁽¹⁾	102" x 29" x 82.25"	2x 9	4 x 3/4	52



LED 3000K



R290 Gas



* 30.2 °F / 41 °F | ** 33.8 °F / 50 °F



Hard wired



230V/60Hz/1-Ph

Important Notes: ⁽¹⁾ 2500 models have 2 connections and 2 digital controls

Performance issues (product temperatures, water on floor, etc.) caused by adverse conditions are not covered by warranty. Keep unit at least 15' from exterior doors, overhead HVAC vents, or any air curtain disruption.

Do not expose unit to direct sunlight or any heat source (ovens, fryers, etc.).

Tile floors, low ceilings, or small rooms will increase noise level.

Compressor air lower front intake. Front panel cannot be blocked.

All technical data, pictures and drawings contained in this document are not binding on the manufacturer, nor can the manufacturer be held liable for any modification of the machine, in part or in whole.